

# Flex™ Decorative Wall Protection

3875 Embassy Parkway  
Fairlawn, OH 44333  
855.753.5474 | koroseal.com

# Thatch

## FACT SHEET

Thatch is enhanced with the colors of a painter's palette. The troweled vertical lines of the texture pick up the colors in rich, brilliant tones. Thatch reminds us of the stolen beauty of the past colored to perfection.

	US UNITS	METRIC UNITS
<b>Total Weight</b>	35 oz. PLY 22.4 oz. PSY	992 g PLM 635 g PSM
<b>Roll Width</b>	52 in.	132 cm.
<b>Backing</b>	Woven	
<b>Federal Spec.</b>	CCC-W-408D, Type III	
<b>WA Spec.</b>	WA-101, Type III	
<b>ASTM F-793</b>	Category V, Type III	
<b>Fire Testing</b>	ASTM E-84, CAN S102M Tunnel Test <sup>1</sup> Class A Rating NFPA 286 - Meets 2006 IBC Section 803.2.1	
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices	
<b>Repeat</b>	Vertical Horizontal Nominal Information Match Information	N/A N/A 52 in. Straight Match, Reverse Hang

<sup>1</sup> When applied to GRC board with A-848-B adhesive

## Available in 8 Colorways

THA1-10 Earnest  
THA1-09 Portrait  
THA1-37 Expectation  
THA1-91 Poplar  
THA1-21 Hope  
THA1-53 Birch Forest  
THA1-43 Sepia  
THA1-98 Smoke