

Flex™ Decorative Wall Protection

3875 Embassy Parkway
Fairlawn, OH 44333
855.753.5474 | koroseal.com

Upland FACT SHEET

This emboss driven pattern speaks to a bold, tiled architectural element, yet is softened by evoking a sense of cushions with a small scale textile texture.

| | US UNITS | METRIC UNITS |
|---------------------------|--|--|
| Total Weight | 35 oz. PLY 22.4 oz. PSY | 992 g PLM 635 g PSM |
| Roll Width | 52 in. | 132 cm. |
| Backing | Woven | |
| Federal Spec. | CCC-W-408D, Type III | |
| WA Spec. | WA-101, Type III | |
| ASTM F-793 | Category V, Type III | |
| Fire Testing | ASTM E-84, CAN S102M Tunnel Test ¹ Class A Rating NFPA 286 - Meets 2006 IBC Section 803.2.1 | |
| Indoor Air Quality | California 01350 – Meets emission requirements for schools and offices | |
| Repeat | Vertical Horizontal Nominal Information Match Information | N/A N/A 52 in. Straight Match, Reverse Hang |

¹ When applied to GRC board with A-848-B adhesive

Available in 8 Colorways

UPL1-12
UPL1-13
UPL1-06
UPL1-01
UPL1-15
UPL1-14
UPL1-19
UPL1-16