

WIDEWALL SELECT

52"-54" Fabric-Backed Vinyl Contract Wallcovering



PHYSICAL PROPERTIES

Weight 15 oz. PLY

Roll Size 52"-54" x 30yds

Backing Scrim

Meets or exceeds Federal Specification CCC-W-408D physical characteristics for Type I Wallcovering

FIRE SAFETY

- └ Class 0/1 – BS476 PART 6/7
- └ Class "A" – ASTM E-84 (GRC)
- └ Tested in accordance with ASTM E-84 Tunnel Test
- └ All pattern meets B1 Chinese Fire standard
- └ Flame Spread 15; Smoke Developed 15

Environmental and Health

WideWall Select is an environmental – green product as it has eliminated all heavy metals such as lead, mercury, cadmium and chromium from the inks and adhesives used. The inks used are highly cleanable waterbased inks.

WideWall Select meets Chinese standard GB18585-2001 for harmful substances in Wallcovering.

BATCHING

Since slight variations in color may occur between different production batches, it is important than in one single area, rolls from the same production batch are used.

OTHER CHARACTERISTICS

- └ A mildew inhibiting additive has been added to help protect against fungal and other microbiological growth.
- └ **WideWall Select** are guaranteed to be free of manufacturing defects for five years.

ORIGIN

China, Designed and Engineered by USA

