# GOODRICH SOLUTIONS WALLCOVERING 159 | SURFACES



FABRIC BACKED VINYL TYPE I

l've got you [ Overed:

**WIDE**WALL 2022 - 2024.12

COMMERCIAL | HOSPITALITY | RESIDENTIAL







52"-54" Fabric-Backed Contract Wallcovering

### PHYSICAL PROPERTIES

**Weight:** 15 oz. PLY / 620 G/PLM

**Roll Size:** 52-54" x 30yds

**Backing**: Scrim

Meets or exceeds Federal Specification CCC-W-408D for Type I Wallcovering

### **FIRE SAFETY**

• Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel test

### **ENVIRONMENTAL AND HEALTH**

**WIDEWALL SURFACES** is an environmental – green product as it has eliminated all heavy metals such as lead, mercury, cadmium and chromium from the inks and adhesives used. The inks used are highly cleanable water-based inks. Widewall Surfaces meets California Section 01350 for Indoor Air Quality Standard.

### OTHER CHARACTERISTICS

- WIDEWALL SURFACES contains a mildew inhibiting agent that has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated.
- **WIDEWALL SURFACES** is guaranteed to be free of manufacturing defects for five years.

### **CLEANING/MAINTENANCE**

Vinyl finishes can be discoloured with the use of caustic cleaners. Thus, we recommend only the use of a mild soap solution for cleaning these products. If stronger cleaning is required, first evaluate the cleaner in an inconspicuous location.

### **BATCHING**

Since slight variations in shading may occur from time to time, it is important that the roll carrying the same batch number be used in any one area.

### ORIGIN

USA



# **LINEN TEXTURE LINEN WAVES** Surface Specification

## **ELEVATED CAIN**



**RAW SILKEN** 



# WIDEWALL **SURFACES** WSF5101 **RAW SILKEN** 54" x 30yds **ROLL SIZE: COMPOSITION:** Vinyl Sheeting **BACKING: WEIGHT:** 15oz PATTERN MATCH: **Reverse Random**

# WSF5102

**RAW SILKEN** 

**ROLL SIZE:** 54" x 30yds

COMPOSITION: Vinyl

**BACKING:** Sheeting

WEIGHT: 15oz













WIDEWALL **SURFACES** WSF5109 **BALINESE** 54" x 30yds **ROLL SIZE: COMPOSITION:** Vinyl **BACKING:** Sheeting 15oz **WEIGHT:** 

PATTERN MATCH:

**Reverse Random** 













# WIDEWALL **SURFACES** WSF5116 **WEAVING BLUR** 54" x 30yds **ROLL SIZE:** Vinyl **COMPOSITION:** Sheeting **BACKING:** 15oz **WEIGHT: PATTERN MATCH: Reverse Random**

WIDEWALL **SURFACES** WSF5117 **WEAVING BLUR ROLL SIZE:** 54" x 30yds Vinyl **COMPOSITION:** Sheeting **BACKING:** 15oz **WEIGHT: PATTERN MATCH: Reverse Random** 

# WIDEWALL **SURFACES** WSF5118 **WEAVING BLUR** 54" x 30yds **ROLL SIZE:** Vinyl **COMPOSITION: BACKING:** Sheeting 15oz **WEIGHT:**

**PATTERN MATCH:** 

**Reverse Random** 

# WSF5119

**DOTTING** 

**ROLL SIZE:** 54" x 30yds

COMPOSITION: Vinyl Sheeting

WEIGHT: 15oz

# WSF5120

### **DOTTING**

**ROLL SIZE:** 54" x 30yds

COMPOSITION: Vinyl Sheeting

WEIGHT: 15oz

# WSF5121

**DOTTING** 

**ROLL SIZE:** 54" x 30yds

COMPOSITION: Vinyl
BACKING: Sheeting
WEIGHT: 15oz

# WSF5122

**DOTTING** 

**ROLL SIZE:** 54" x 30yds

COMPOSITION: Vinyl
BACKING: Sheeting
WEIGHT: 15oz

# WSF5123

**DOTTING** 

**ROLL SIZE:** 54" x 30yds

COMPOSITION: Vinyl Sheeting

WEIGHT: 15oz































### WSF5139

### LINEN TEXTURE

**ROLL SIZE:** 54" x 30yds

**COMPOSITION:** Vinyl Sheeting

WEIGHT: 15oz

### WSF5140

### LINEN TEXTURE

**ROLL SIZE:** 54" x 30yds

COMPOSITION: Vinyl Sheeting

WEIGHT: 15oz

### WSF5141

### LINEN TEXTURE

**ROLL SIZE:** 54" x 30yds

**COMPOSITION:** Vinyl Sheeting

WEIGHT: 15oz







### WSF5145

**ELISE** 

**ROLL SIZE:** 54" x 30yds

**COMPOSITION:** Vinyl

**BACKING:** Sheeting

WEIGHT: 15oz

# WIDEWALL **SURFACES** WSF5146 **ELISE** 54" x 30yds **ROLL SIZE: COMPOSITION:** Vinyl Sheeting **BACKING:**

**WEIGHT:** 

15oz

### WSF5147

**ELISE** 

**ROLL SIZE:** 54" x 30yds

COMPOSITION: Vinyl

**BACKING:** Sheeting

WEIGHT: 15oz

WIDEWALL **SURFACES** WSF5148 **CIRRUS** 54" x 30yds **ROLL SIZE: COMPOSITION:** Vinyl **BACKING:** Sheeting **WEIGHT:** 15oz PATTERN MATCH: **Reverse Random** 

WIDEWALL **SURFACES** WSF5149 **CIRRUS ROLL SIZE:** 54" x 30yds **COMPOSITION:** Vinyl **BACKING:** Sheeting **WEIGHT:** 15oz Reverse Random PATTERN MATCH:

# WIDEWALL **SURFACES** WSF5150 **CIRRUS ROLL SIZE:** 54" x 30yds **COMPOSITION:** Vinyl **BACKING:** Sheeting **WEIGHT:** 15oz Reverse Random PATTERN MATCH:



## WIDEWALL (INDEX) SURFACES

	Pattern No	Pattern Name	Weight (oz)	Pattern Repeat (In)				
Page				Horizontal	Vertical	Pattern Match	Backing	Roll Size
1	WSF5101	RAW SILKEN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
2	WSF5102	RAW SILKEN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
3	WSF5103	RAW SILKEN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
4	WSF5104	RAW SILKEN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
5	WSF5105	SHIMMER	15	0	0	Straight/Random	Scrim	52" - 54" x 30yds
6	WSF5106	BALINESE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
7	WSF5107	BALINESE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
8	WSF5108	BALINESE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
9	WSF5109	BALINESE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
10	WSF5110	BALINESE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
11	WSF5111	BALINESE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
12	WSF5112	BALINESE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
13	WSF5113	WEAVING BLUR	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
14	WSF5114	WEAVING BLUR	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
15	WSF5115	WEAVING BLUR	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
16	WSF5116	WEAVING BLUR	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
17	WSF5117	WEAVING BLUR	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
18	WSF5118	WEAVING BLUR	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
19	WSF5119	DOTTING	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
20	WSF5120	DOTTING	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
21	WSF5121	DOTTING	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
22	WSF5122	DOTTING	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
23	WSF5123	DOTTING	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
24	WSF5124	LINEN WAVES	15	0	12	Straight/Random	Scrim	52" - 54" x 30yds
25	WSF5125	LINEN WAVES	15	0	12	Straight/Random	Scrim	52" - 54" x 30yds
26	WSF5126	LINEN WAVES	15	0	12	Straight/Random	Scrim	52" - 54" x 30yds
27	WSF5127	LINEN WAVES	15	0	12	Straight/Random	Scrim	52" - 54" x 30yds
28	WSF5128	ELEVATED CAIN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
29	WSF5129	ELEVATED CAIN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
30	WSF5130	ELEVATED CAIN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
31	WSF5131	ELEVATED CAIN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
32	WSF5132	ELEVATED CAIN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
33	WSF5133	ELEVATED CAIN	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
34	WSF5134	CHIN STRAWS	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
35	WSF5135	CHIN STRAWS	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
36	WSF5136	CHIN STRAWS	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
37	WSF5137	CHIN STRAWS	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
38	WSF5138	CHIN STRAWS	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
39	WSF5139	LINEN TEXTURE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
40	WSF5140	LINEN TEXTURE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
41	WSF5141	LINEN TEXTURE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
42	WSF5142	MATRIX	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
43	WSF5143	MATRIX	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
44	WSF5144	MATRIX	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
45	WSF5145	ELIS E	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
46	WSF5146	ELISE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
47	WSF5147	ELISE	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
48	WSF5148	CIRRUS	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
49	WSF5149	CIRRUS	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
50	WSF5150	CIRRUS	15	0	0	Reverse/Random	Scrim	52" - 54" x 30yds
		ļ	1			1		

#### **Installation and Maintenance Guidelines**

#### **BEFORE YOU BEGIN**

Examine the material carefully to ensure that the pattern, colour, and quality are satisfactory and as ordered. Check that the quantity and dimensions match the required specifications, prior to cutting. In the event that any discrepancies are found, STOP and contact Goodrich Global before proceeding.

We recommend that the wall moisture content does not exceed 4% using a reputable moisture meter, and that active moisture infiltration, condensation, and/or accumulation - particularly in warm, humid climates - is not present. If walls show mould, mildew or visible moisture damage, or if moisture content exceeds recommendations, do not proceed with installation until the condition has been fully corrected under the direction of a qualified professional. Goodrich Global will not be responsible for any performance or quality issues if moisture problems are not addressed before or following installation.

#### **HANGING GUIDELINES**

Wallcovering rolls are numbered consecutively and should be cut and installed in reverse sequence, starting with the highest numbered roll. All strips should be hung in sequence as they are cut from the roll, using full widths of material, whenever possible. Install the wallcovering under permanent lighting conditions to evaluate colour and texture uniformity.

When hanging non-reversible or matching patterns, measure the wall height, allowing for pattern match, add 4", and table trim using a straight edge to ensure alignment across seams. Large, dominant pattern repeats require more careful planning as far as starting point, ceiling line, chair rails, door/window headers, etc. Patterns are meant to match at eye level and may run off slightly at the top and bottom of the wall. When hanging textured or random-match patterns, reverse hang alternate strips for a more uniform appearance; overlap and double cut, being careful not to score the wall. If the pattern effect is not acceptable after three strips are hung, re-hang strip #2 without reversing.

If any defect, colour variation, or unacceptable pattern effect is noticeable after three panels are cut and hung, STOP and contact Goodrich Global immediately. Goodrich Global cannot accept any claims on labour or material after more than three lengths have been installed.

#### **ADHESIVE APPLICATION**

Apply a uniform coat of a premixed vinyl wallcovering adhesive to the back of the material using a short-napped paint roller or stiff bristle brush (a pasting machine can be used at the installer's discretion). Goodrich WA202 adhesive is recommended for heavyweight vinyl wallcovering. Fold each sheet over and allow up to 10 minutes booking time for the adhesive to penetrate the backing of the lightweight vinyl material (up to 15 minutes for heavyweight vinyl), and to avoid paste drying at the edges.

**WA202** 

Wallcovering

Adhesive

#### **Goodrich WA202 Wallcovering Adhesive:**

- Specially formulated for all types of contract wallcoverings
- Non Hazardous, Non Toxic, Non Flammable, Non-Staining
- Solvent Free and Formaldehyde Free
- VOC is 0.45mg/kg
- Made in England



#### Complies to:

- ✓ Regulation (EC No 1907/2006)
- CLP European Regulation (EC) No 1272/2008
- **S**3046/1981



Hang the first strip to a plumb line, overlapping the ceiling and baseboard, within 12 minutes of paste application. Use a stiff bristle brush to ensure that the wallcovering makes contact with the wall. A plastic smoother can also be used on non-metallic Vinyls, providing only light pressure is applied (do not use sharp-edged tools). Smooth from the middle to the outside edges, being careful not to stretch the material, and work out all air bubbles. Trim at the ceiling and baseboard with a sharp razor blade. For matched patterns, butt the second strip to the edge of the first and smooth out firmly. When double cutting non-matching patterns, place a 2-3" wide strip behind the seam to avoid scoring the wall. Flatten seams exerting light pressure with a seam roller. Lowadhesive painter's tape can be used to keep the face of the seams clean. Before applying the next strip, trim the top and bottom as with the first panel, and proceed in the same manner around the room.

Avoid cutting narrow widths of material for placement above doors and below windows. Vertical joints should not occur less than six inches from inside or outside corners. When trimming at chair rails and ceilings, always use a broad knife rather than a straight edge. Take extra care in keeping the adhesive off the face of the wallcovering.

Remove excess adhesive immediately with a natural sponge, frequently rinsed in clear, warm water, and dry with a soft, lint free cloth. After installation, the walls and wallcovering should be monitored for potential moisture or vapour infiltration, which must be promptly eliminated.

#### **MAINTENANCE**

Most wallcovering is easily cleaned using clear, warm water and mild soap with a natural sponge. A soft cloth or towel should only be used to tamp dry (do not rub). Stubborn stains can be removed with a laundry spot remover or rubbing alcohol. Do not use solvent-based cleaning agents, lacquer thinners, nail polish remover, pine oil, or cleaning agents containing bleach, which may cause discoloration over time.

Note: The above is intended only as a guideline. Wallcovering installations must conform to current hanging instructions included with each shipment. The installer has final responsibility for proper installation and evaluation of jobsite conditions.

### **GOODRICH SOLUTIONS** WALLCOVERING 159 | SURFACES

### WITH GOODRICH,

Your habitat becomes

A gallery of Your self-expressions;

A canvas for Your **creativity**;

A space for Your **SOU**;

A showcase of Your taste for life;

f /Goodrich.Global.Singapore / /goodrich\_global in /GoodrichGlobal / /GoodrichChina 

(Goodrich\_Global