

# WIDEWALL VIBRANT

54" Fabric-Backed Vinyl Contract Wallcovering

## PHYSICAL PROPERTIES

---

<b>Weight</b>	15 oz. PLY
<b>Roll Size</b>	54" x 30yds
<b>Backing</b>	Sheeting

Meets or exceeds Federal Specification CCC-W-408D physical characteristics for Type I Wallcovering

## FIRE SAFETY

---

- Class 0/1 – BS476 PART 6/7
- Class "A" – ASTM E-84  
Flame Spread 15; Smoke Developed 30

## ENVIRONMENT AND HEALTH

---

- **WideWall Vibrant** is an environmental – green product as it has eliminated all heavy metals such as lead, mercury, cadmium and chromium.

## BATCHING

---

Since slight variations in color may occur between different production batches, it is important that in one single area, rolls from the same production batch are used.

## OTHER CHARACTERISTICS

---

- Contain antimicrobial additives to resist the growth of mildew and bacteria. Passed ASTM G21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.
- **WideWall Vibrant** is supplied with a 5 years warranty against manufacturing defects.

## ORIGIN

---

Made in Thailand, Designed in USA

HIDE

