ONEWOOD SOLID FLOORING



Flooring is an important component of every interior space and timber has always been a popular choice for flooring due to its natural grains and colour.

ONEWOOD flooring is a unique product that excels in durability and dimensional stability as compared to natural timber. Its natural wood grains add warmth to your living space.

ONEWOOD Flooring Properties



Features



Suitable for High Traffic

ONEWOOD is a product with high density and hence resistant to areas with high traffic. Together with compatible flooring finishes, the durability of ONEWOOD Flooring is enhanced, suitable for commercial places like offices and shopping centres.



Reuse and Refurbish

ONEWOOD Flooring's homogeneous property enables resanding to reveal a fresh layer of beautiful wood grains that can be recoated for maintenance or to achieve a new look to complement your new design.

Standard Dimensions

Thickness mm	Surface mm B	Width mm	Tongue mm D
12	140	145	5
15	140	145	5
18	140	145	5



Section – Typical Tongue and Groove Profile

ONEWOOD Flooring is available in wide dimensions up to 210 mm width.



Wear Protection

For areas where high traffic is expected, ONEWOOD Flooring can be coated with an additional layer of flooring finish for much improved wear, chemical and moisture resistance to your floor.

Installation

ONEWOOD Solid Flooring can be installed by laying on screed / concrete, batten and plywood base. For technical details and drawings, kindly contact us for information.

Flooring Finishes



Natural



Clear



Golden Teak



Matured Teak







