



# PREMIERWALL FUSION LOW VOC

50 - 54" Fabric-Backed Contract Wallcovering

## PHYSICAL PROPERTIES

Weight 20/21 oz. PLY  
Roll Size 50/54" x 30yds  
Backing Osnaburg

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

## FIRE SAFETY

- Class "A" Fire rated
- NFPA255 (UL723, CAN S102M) Tunnel Test1
- NFPA 286 Corner Burn Test2
- Meets requirements for Flame Spread, Smoke Developed and Flashover
- UL Labelled and Listed

## ENVIRONMENT & HEALTH

- The product has been assessed according to the assessment criteria of the Singapore Green Building product certification scheme.
- Meets California section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 point for regional materials



## ANTI-MICROBIAL FEATURES

**PREMIERWALL FUSION** contain mildew and staph resistant additives in the vinyl and plastisol. This provides the wallcovering with resistance to the growth of mildew and bacteria, including mold, fungi, pink stain and black fungal stain.

## BATCHING

Since slight variation in shading may occur time to time, it is important that the roll carrying the same batch number be used in any one area.

## ORIGIN

USA

