



**AZ53967LL** Taupe Tempo

54"/Type II/ 20 oz. **LOW VOC** **RECYCLED CONTENT**



Render Ready Tiles available

**PHYSICAL PROPERTIES**

**Weight:** 20 oz. PLY, 620 G/PLM 13.3 oz. PSY, 451 G/PSM

**Backing:** Osnaburg

**Width:** 54 in./137 cm

**Match:** Reverse Random

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering  
Custom colors, weights, and micro venting available.

**FIRE SAFETY**

Class "A" Fire rated (ASTM E-84)

See website or contact us for additional results

Product Specifications, Fire Safety & Ratings, Environment & Health  
and Warranty is available at [symphonywallcovering.com](https://www.symphonywallcovering.com)

**ENVIRONMENTAL**

- Meets CA CDPH Standard Method v1.2 (Low VOC)
- 10% recycled content
- EPD/HPD
- NSF/ANSI 342 certified
- Non-phthalate
- Meets RoHS, REACH, TSCA, and Prop 65 requirements

**CLEANABILITY**

- Inherent anti-microbial protection
- Withstands hospital-grade cleaners & disinfectants
- Available as a custom with **INVISICAP** | complete **chemical** protection